ENCHANTED ELEGANCE

MATERIAL TYPE: LVP

RegalCraft
WHERE TIMELESS ELEGANCE MEETS CRAFTSMANSHIP

RC-EE12 Sunkissed Refuge

Water Proof	Indent Resistant	Sound Tested	Paw Friendly	Formaldehyde Free	Phthalate Free

RegalCraft proudly presents "Enchanted Elegance," a collection that encapsulates the very essence of nature's captivating beauty. Radiating sophistication and charm, each piece within this collection is a testament to the allure that defines our brand. "Enchanted Elegance" transforms every space into a realm of timeless enchantment, where every step taken exudes grace and style. With meticulous craftsmanship and unparalleled design, this collection evokes a sense of wonder and refinement that transcends the ordinary. Elevate your surroundings with the magic of "Enchanted Elegance," as RegalCraft continues to set the standard for captivating and sophisticated interiors.

Material Type	
Luxury Vinyl Plank (LVP)	
Plank Size	
7.25" × 48"	
Total Thickness	**Wear Layer**
2 mm	6 mil
Edge Profile	
Square Edge	
Plank Repeat	
5	
Texture/Style	
Wood Grain Embossed	
Finish	
UV Aluminum Oxide	
Installation Type	
Glue Down	

Per Box	SQFT	Lbs.
22 pieces	53.17	42
Per Pallet	**SQFT**	**Lbs.**
50 boxes	2,658.71	2,180
Per Container	**SQFT**	
1,000 boxes	53,170	
Pallet Dimensions (L × W × H)		
49" × 39" × 26"		

LIMITED WARRANTY **15** YEARS RESIDENTIAL

LIMITED WARRANTY **7** YEARS COMMERCIAL

Regal-Craft.com

ENCHANTED ELEGANCE

RegalCraft

COLORS

RC-EE01 Blossom Brook

RC-EE02 Waterfall Whispers

RC-EE03 Solitary Stone

RC-EE04 Pristine Prairie

RC-EE05 Earthly Dusk

RC-EE06 Verdant Valley

RC-EE07 Oasis Opulence

RC-EE08 Radiant Ferns

RC-EE09 Sunrise Shores

RC-EE10 Marigold Moon

RC-EE11 Wisping Vistas

RC-EE12 Sunkissed Refuge

TESTING

Fire Rating	ASTM E648	Class 1
Surface Friction (in BPN)	ASTM E303	Dry 77
Size and Squareness	ASTM F2421	Above Average
IIC - Impact Sound Rating	E492	39 db
STC - Sound Transmission Loss	E90	53 db
Stain Resistance	ASTM D1308	No Stain

Average Wear Layer Thickness	ASTM F410	6.0 mil
Dimensional Stability, Curl After Heat	ASTM F2199	Passes
Residual Indentation, Surface Integrity	ASTM F1914	Passes
Resistance to Heat	ASTM F1514	Passes
Resistance to Light	ASTM F1515	Passes

Floor Score Certified

Phthalate Free

floor score

CERTIFIED BY SCS Global Services