

HERITAGE GLEAM

MATERIAL TYPE: SPC



RC-HG02 Riverbank Reflections



Water Proof



Indent Resistant



Sound Tested



Paw Friendly



Formaldehyde Free



Phthalate Free

Introducing "Heritage Gleam," an exquisite collection by RegalCraft that harmonizes the enduring legacy of our brand with a fusion of nature's timeless aesthetics and cutting-edge technology. This collection is a testament to the seamless marriage of classic natural beauty and modern innovation, resulting in flooring that resonates with both heritage and the future. Each piece within "Heritage Gleam" is a work of art, encapsulating the essence of timelessness while incorporating state-of-the-art technology for enhanced durability and ease of maintenance. Elevate your interiors with the legacy and allure of "Heritage Gleam," as RegalCraft continues to bridge the gap between the past and the present, redefining the very essence of sophistication and style.

Material Type	
SPC Rigid Core	
Plank Size	Wear Layer
9" x 60"	20 mil
Total Thickness	Edge Profile
6.5 mm	Painted Bevel
Core Thickness	Plank Repeat
5 mm	5
Pad Thickness	Attached Pad
1.5 mm	Yes
Pad Type	
Pressed and Sealed EVA	
Texture/Style	
Wood Grain Embossed	
Installation Type	
Uniclic/Floating	Finish
UV Acrylic	

Per Box	SQFT	Lbs.
8 pieces	30.51	49
Per Pallet	SQFT	Lbs.
44 boxes	1,342.23	2,224
Per Container	SQFT	
924 boxes	28,191.24	
Pallet Dimensions (L x W x H)		
62" x 38" x 31"		



HERITAGE GLEAM



COLORS



RC-HG01 Fronds Fern



RC-HG02 Riverbank Reflections



RC-HG03 Sycamore Symphony



RC-HG04 Petal Path



RC-HG05 Harmony Haven



RC-HG06 Crisp Clover



RC-HG07 Serene Sienna



RC-HG08 Mountain Majesty



RC-HG09 Horizon Lullaby



RC-HG10 Mossy Morning



RC-HG11 Rainforest Rain



RC-HG12 Reverie Retreat

MOULDINGS



End Cap



Flush Stair Nose



Quarter Round



Reducer



Stair Tread



T-Moulding

TESTING

Fire Rating	ASTM E648	Class 1
Coefficient of Friction	ASTM D2047	Standard Neolite 0.90
Static Load Limit	ASTM F970	0.005 in.
IIC - Impact Sound Rating	E492	59 db
STC - Sound Transmission Loss	E90	53 db
Overall Thickness	ASTM F387	0.264 in.
Average Wear Layer Thickness	ASTM F410	19.9 mil
Dimensional Stability, Curl After Heat	ASTM F2199	Passes
Residual Indentation, Surface Integrity	ASTM F1914	Passes
Resistance to Heat	ASTM F1514	Passes
Resistance to Light	ASTM F1515	Passes

Floor Score Certified

Phthalate Free



CERTIFIED BY
SCS Global Services