

REGAL RESERVE

MATERIAL TYPE: SPC



RC-RR06 Arctic Azure



Water Proof



Indent Resistant



Sound Tested



Paw Friendly



Formaldehyde Free



Phthalate Free

Introducing “Regal Reserve” by RegalCraft – a collection that defines the epitome of nature’s opulence and endurance, meticulously curated for the most distinguished interiors. Representing a blend of luxury and lasting durability, “Regal Reserve” captures the essence of exclusivity and unparalleled quality. This collection is a testament to our commitment to providing only the finest, where each floor is a masterpiece that transforms spaces into regal domains. With “Regal Reserve,” RegalCraft sets a new standard of elegance and endurance, ensuring that your interiors exude magnificence for years to come. Elevate your surroundings with the grandeur of “Regal Reserve,” where luxury meets lasting legacy.

Material Type	
SPC Rigid Core	
Plank Size	Wear Layer
7” x 48”	12 mil
Total Thickness	Edge Profile
5 mm	Micro Bevel
Core Thickness	Plank Repeat
4 mm	5
Pad Thickness	Attached Pad
1 mm	Yes
Pad Type	
Pressed and Sealed EVA	
Texture/Style	
Wood Grain Embossed	
Installation Type	Finish
Uniclic/Floating	UV Acrylic

Per Box	SQFT	Lbs.
12 pieces	27.87	47
Per Pallet	SQFT	Lbs.
50 boxes	1,393.40	2,408
Per Container	SQFT	
900 boxes	25,083	
Pallet Dimensions (L x W x H)		
49” x 39” x 33”		



REGAL RESERVE



COLORS



RC-RR01 Orchid Ocean



RC-RR02 Oakwood Oasis



RC-RR03 Blooming Fields



RC-RR04 Jasmine Ivy



RC-RR05 Meadow Magic



RC-RR06 Arctic Azure



RC-RR07 Stormy Terrace



RC-RR08 Cavern Crater



RC-RR09 Autumn Aura



RC-RR10 Weaving Waterscapes



RC-RR11 Ruby Twilight



RC-RR12 Gossamer Glow

MOULDINGS



End Cap



Flush Stair Nose



Quarter Round



Reducer



Stair Tread



T-Moulding

TESTING

Fire Rating	ASTM E648	Class 1
Coefficient of Friction	ASTM D2047	Standard Neolite 0.95
Static Load Limit	ASTM F970	0.003 in.
IIC - Impact Sound Rating	E492	59 db
STC - Sound Transmission Loss	E90	53 db
Overall Thickness	ASTM F387	0.195 in.

Average Wear Layer Thickness	ASTM F410	15.2 mil
Dimensional Stability, Curl After Heat	ASTM F2199	Passes
Residual Indentation, Surface Integrity	ASTM F1914	Passes
Resistance to Heat	ASTM F1514	Passes
Resistance to Light	ASTM F1515	Passes

Floor Score Certified

Phthalate Free



CERTIFIED BY
SCS Global Services